



TECHNICAL DATA

TEMP. RANGE [°C]	TEMPERATURE CLASS	AMBIENT CONDITIONS [°C/RH]	EXPOSITION SURFACE [m ²]	DIMENSIONS [mm - l × d × h]	POWER SUPPLY [V/Hz]	DEMAND FOR COOLING CAPACITY [W/mb]	NET WEIGHT [kg]	REFRIGERANT
+1...+5	3M1	+25/60%	3,1	3750 × 1130 × 1200	230/50	370	410	R448A/R449A

STANDARD

- Remote version (external compressor)
- Electronic control with digital display of temperature
- Dynamic cooling
- Device dedicated for individual build-over (without external body) with possibility to in-line arrangement
- Drop-in version
- Plexiglass back-covers
- Worktop made of stainless steel AISI 304
- Side-opened front square glass
- Front bumper
- Exterior painted by powder
- Exposition surface made of stainless steel AISI430
- Siphoned condensate drains
- Top LED lighting - white (warm) color

OPCJE

- Customer front shelf
- LED illuminated exposition - meat light (red light)
- Defrosting: defrost heater

BOLARUS S.A. does not assume any liability concerning the topicality of the data contained in this document. Graphic materials and photos may slightly differ from their actual appearance.